

Order number: 01 113 06 99

## SCHELL infrared exposed urinal flush valve unit SCHELLTRONIC, DN 15

battery operation, capable of being parameterised by SSC

### Scope of delivery:

- infrared exposed urinal flush valve with isolating valve
- electronic module programmable
- battery compartment integrated in fitting
- 4 x AAA alkaline batteries
- 6 V solenoid valve in cartridge design with integrated pre-filter
- flush pipe  $\varnothing$  18 x 193 mm
- Urinal inner connector

### Field of application / Technical data:

- flow pressure: 1 to 5 bar
- flow volume: 0,3 l/s according to DIN EN 12541
- adjustable by means of short range reflex
  - flow time: 1 - 15 seconds adjustable
  - sensor range short, medium, long
  - stagnation flush Out, On 30 s every 24 h after last flush / every 24 h
  - pre-flush: Out, On 1s
  - automatic stadium operation: Out, On
  - odour trap flush: Out, On
  - expanded setting options with SCHELL Software SSC
    - flow time: 1 - 15 seconds adjustable
    - sensor range short, medium, long
    - stagnation flush time 24 h after last flush, every 24 h (adjustable 1 - 240 h) flush time: 30 s (adjustable 5 - 600 s)
    - pre-flush: 1 s (adjustable 5 - 60 s after last use)
    - automatic stadium programm 1 s/ user (adjustable 20 - 60 s after last use)
    - odour trap: on 1 h (adjustable 1 - 240 s after last use)
    - energy - saving mode: active after 1h (adjustment range : out, 1 - 254 h)

### Details:

- Material:

parts in contact with water conform German drinking water regulation

- Test Mark: PA-IX 8952/II, WELL Public
- Surface: chrome
- Weight: 1.24 kg/pc.
- Packaging unit: 1
- Dimension: DN 15 G 1/2 ext. thread

### Recommended associated item:

Flush pipe $\varnothing$ 18 mm	Order No.: <a href="#">50 722 06 99</a>	or
Flush pipe $\varnothing$ 18 mm edged	Order No.: <a href="#">50 223 06 99</a>	or
Urinal external connector	Order No.: <a href="#">27 820 06 99</a>	
SSC Bluetooth®-Module	Order No.: <a href="#">00 916 00 99</a>	or
SSC USB-adapter	Order No.: <a href="#">01 586 00 99</a>	

