

Order number: 03 995 03 99

## SCHELL frost-resistant outdoor tap POLAR II

complete tap for subsequent installation  
frost-resistant valve seat 200 mm from leading edge of stonework

automatic bleeding of pipe at every shut-off  
without anti-vacuum device. For installation with collection locking device

### Scope of delivery:

- square-drive spigot and operation handle
- backflow preventer (BP, EN 1717: EB)
- wall bracket mounting with mounting accessories
- connection: G 1/2 external thread/ 15 mm copper pipe
- surface mattchrome
- wall conduit with insulation hose

### Field of application / Technical data:

- for installation in wall conduit
- bore diameter  $\varnothing$  38 mm

### Details:

- Material: brass conform German drinking water regulation
- Test Mark: P-IX 19319/II
- Noise Class: II
- Surface: matt chrome
- Weight: 1.33 kg/pc.
- Packaging unit: 1
- Dimension: DN 15 G 1/2" ext. thread/ $\varnothing$  15

### Versions:

Dimension: DN 15 G 1/2 ext. thread/ $\varnothing$  15      Order No.: [03 996 03 99](#)  
with anti-vacuum device version C. Safety combination  
in accordance with EN 1717, approved acc. to VP 648,  
DVGW registration no. CL0257 (whole fitting), matt  
chrome, PU 1, W: 1.56 kg/pc.

### Recommended associated item:

sanitary handle SECUR protects against unauthorised      Order No.: [48 006 06 99](#)  
withdrawal of water

