

HAIR DRYER

Hair dryer, gun model, push-button with plug

Código: SC0010CS

General description

- · Warm air hair dryer.
- · Gun-like, connected to the wall-mounted holder.
- Operated by an on/off switch.
- Small-size appliance.
- · Highest electrical safety.
- · Suitable for hotel bathrooms.


Components and Materials

- · Black, steel-like ABS hand piece which incorporates polypropylene air concentrator and ON/OFF switch.
- · Cabel and plug from the holder, 1 m length
- · Spiral cord, 650-1.800 m length, from the holder to the hand
- Wall-mounted holder for permanent installation, incorporates 1 hole for mounting on the wall.
- · Two speed settings
- · Motor, 7.500-10.000 rpm, includes a thermal overload switch.
- · Polycarbonate turbine.



Voltage - 220-240 V	Motor power - 40 W
Electrical isolation - clase	Heating element power - 1200 W
П	Consumption - 2,7-4,9 A
Frequency - 50 Hz	RPM - 7.500-10.000
Electrical isolation - Clase	Air temperature(10 cm distance /
П	21 °C) - 61 °C
Dimensions - 150x210x79	Noise level (at 2 m) - 60 dB
mm	Spiral cordset length - 650-1.800
Weight - 0,700 Kg	mm
Effective airflow - 73 m ³ /h/	Installation height - 1300-1500
1.217 l/min	mm
Air velocity - 54 Km/h	
Total power - 540-1.200 W	





Dim.: ±4%

Operation

Remove gun-like hand piece from holder and move the switch to the ON position. Press the bottom on the handle for its working. Select the speed and direct the hand piece to the hair at your own convenience. Once you are finish, hang the gun-like hand piece in the support and switch to the OFF position.

Certificates & Qualifications

ISO 9001:2008, VDE.

COMPLIANT WITH ELECTRICAL SAFETY DIRECTIVES

Warm air hair dryer should be made of black, steel-like ABS and provided with a wall-mounted holder where it is connected to. The white ABS hand piece should incorporate a polypropylene air concentrator and an ON/OFF switch. The spiral cord should be 650 1.800 mm, with plug from the holder. The wall-mounted holder should incorporate 1 hole for mounting on the wall. Motor, 7.500-10.000 rpm, should include a thermal overload switch. Overall dimensions shall be 150 x 210 x 90 mm. Unit should be VDE approved and CE marked and comply with electrical safety directives 73/23/CEE & 93/68/CEE and electro-magnetic compatibility directives 89/336/CEE & 92/31/CEE.

Hair dryer shall be model SC0010CS push-button operated ABS cover, of Mediclinics S.A., C/Industria 54, E-08025 Barcelona, Spain.

Mediclinics, S.A., reserves the right to make changes and/or modifications to the products and their specifications without prior notice.

